



Mobilmet 440 Series

Mobil Industrial , Russia

High Performance Oil-Based Cutting Fluids

Product Description

Mobilmet 440 Series fluids are high performance, multi-service, non-corrosive straight cutting fluids. They are designed for moderate to heavy duty cutting operations. They are also suitable for machine tool lubrication and use as hydraulic fluids in specific applications. They are formulated from high quality base oils and chlorine-free additives to provide effective machine performance in a wide variety of moderate to severe operations. They are non-staining to both ferrous and non-ferrous metals during machining. Mobilmet 440 Series fluids are formulated to prevent the formation of oil mist in the vicinity of the machine tool, thus contributing to a safer and more pleasant working environment.

Features and Benefits

Mobilmet 440 Series Fluids are designed for a very wide variety of non-corrosive cutting and machining operations that range from moderate to severe. They provide long service life, improved tool life and lower reject rates. They are multi-purpose cutting oils that are also suitable for machine tool lubrication and use as hydraulic fluids. These features help minimize the effects of cross contamination and reduce the costs associated with unscheduled fluid change-outs or reduced machine and tool performance.

Features	Advantages and Potential Benefits
Multi-service characteristics	Reduced cross-contamination problems
	Reduced waste and lower maintenance
Non-corrosive / non-staining	Improved quality of finished materials
Highly effective machining performance	Longer tool life and reduced downtime
	Improved surface finish and fewer rejects

	Increased feed rates and machine speeds
Effective anti-mist characteristics	Cleaner and safer working environment

Applications

Mobilmet 440 Series fluids are recommended for a wide range of moderate to severe machining operations on all types of metals. Mobilmet 443 is recommended for machining non-ferrous metals and their alloys, normal to difficult-to-machine steels, including cementation steels, carbon steels and high alloy steels. Mobilmet 446 and Mobilmet 447 are recommended for severe duty gear hobbing, gear cutting and shaving, gear and thread grinding, milling, and broaching operations.

Typical Properties

Mobilmet 440 Series	443	446	447
Viscosity, ASTM D 445			
cSt @ 40° C	15.3	32.6	45.9
cSt @ 100° C	3.8	6.0	7.4
Viscosity Index, ASTM D 2270	145	132	124
Pour Point, °C, ASTM D 97	-33	-24	-33
Flash Point, °C, ASTM D 92	170	190	220
Specific Gravity @15° C kg/l, ASTM D 4052	0.86	0.88	0.89
Copper Strip Corrosion, ASTM D 130, 3 hrs @ 100° C, max	2A	2A	2A

Health and Safety

Based on available information, this product is not expected to produce adverse effects on

health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment. Switzerland use: Toxicity class: free BAG T No.: 611500

The Mobil logotype, the Pegasus design, and Mobilmet are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

ExxonMobil Lubricants & Specialties Europe, подразделение ExxonMobil Petroleum & Chemicals BVBA. Настоящая информация относится только к продуктам, поставляемым в Европу, включая Турцию, и страны бывшего Советского Союза.

ООО «Мобил Ойл Лубрикантс» : 123242, Москва, Новинский бульвар, д.31

Вы всегда можете связаться с нами по вопросам, касающихся продуктов Mobil, а также сервисных услуг: <https://www.mobil.ru/ru-ru/contact-us-technical>

+ 7 (495) 232 22 23

Указанные значения показателей являются типичными для результатов, лежащих в пределах нормальных производственных допусков, но не являются составной частью спецификации или норм. На обычном производстве и при изготовлении на разных заводах возможны отклонения, которые не влияют на эксплуатационные характеристики. Содержащаяся здесь информация может быть изменена без уведомления. Не все продукты могут быть доступны на местном рынке. За дополнительной информацией обращайтесь к местному представителю ExxonMobil или посетите www.exxonmobil.com

ExxonMobil включает в себя множество аффилированных и дочерних компаний, многие из которых содержат в своем наименовании Esso, Mobil или ExxonMobil. Ничто в настоящем документе не подразумевает отмену или преобладания над корпоративной независимостью местных организаций. Ответственность и отчетность за действия на местах остаются за местными аффилированными организациями ExxonMobil.

Energy lives here™

ExxonMobil

Exxon

Mobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved